



B° Sancholopetegui, 22  
 Apdo. 17  
 20560 OÑATI (ESPAÑA)  
 Tel: +34 943 71 80 30  
 Fax: +34 943 71 81 81  
 ---  
 www.fagorindustrial.com

## DISHWASHER, FI-100

### DESCRIPTION

Made of stainless steel.  
 Hourly production: 1000 dishes/h.  
 Wash cycles: 55", 75", 105".  
 Rotating wash and rinse systems.  
 Two independent wash pumps for lower and upper systems,  
 590 W each.  
 Heated by means of shielded elements.  
 Tank with 4,5 kW heating element.  
 Built-in rinse water boiler (9 kW).  
 Automatic rinse dispenser.  
 Thermostatically adjusted. (wash temperature: 60 °C).  
 Safety thermostat.  
 Safety switch for hood opening.  
 Adjustable legs.  
 Baskets equipment: 1 x CT-10, 1 x CP-16/18 and 8 cutlery  
 containers.  
 Power: 14.7 kW.  
 Dimensions: 675 x 675 x 1400 mm.

Baskets equipment: 1 x CT-10, 1 x CP-16/18, 1 x CB-7 and  
 4 cutlery containers.  
 Power: 6.65 kW.  
 Dimensions: 600 x 600 x 1.200 mm.

### DATA

Electric power	kW	14,7	Water consumption	lit/h	60
Electrical intake			Water pressure	Kg/cm <sup>2</sup>	2 - 4
230V - 1 + N + T	2x16+T - 80 A		Steam power	kg/h	
230V - 3 + T	3x10+T - 50 A		Steam pressure	Kg/cm <sup>2</sup>	
400V - 3 + N + T	4x4+T - 32 A		Air consumption	Nl/min	
Gas power	kcal/h		Air pressure	Kg/cm <sup>2</sup>	
Gas power	kW		Length	mm	675
Natural Gas Consumption	m <sup>3</sup> /h		Depth	mm	675
Natural Gas pressure	g/cm <sup>2</sup>		Height	mm	1400
LPG Consumption	Kg/h		Net weight	kg	116
LPG pressure	g/cm <sup>2</sup>		Gross weight	kg	132
			Volume	m <sup>3</sup>	0,876



Distribuidor oficial: