



B° Sancholopetegui, 22
 Apdo. 17
 20560 OÑATI (ESPAÑA)
 Tel: +34 943 71 80 30
 Fax: +34 943 71 81 81

 www.fagorindustrial.com

DISHWASHER, FI-72

DESCRIPTION

Made of stainless steel.
 Hourly production: 720 dishes/h.
 Maximum diameter of dishes: Ø 42 cm.
 Valid for self-service trays.
 Wash cycles: 90" and 180" fixed.
 Rotating wash and rinse.
 Heated by means of shielded elements.
 Built-in rinse water boiler.
 Tank with 2.8 kW heating element.
 Tank capacity: 25 litres.
 Boiler with 6 KW heating element.
 Water consumption: 2.7 litres/rinse.
 Automatic rinse dispenser.
 Thermostatically adjusted. (wash temperature: 60 °C).
 Thermometers for wash and rinse water temperature.
 Safety thermostat.
 Filters and trays in the wash tank.
 Safety switch for door opening.
 Adjustable legs.

Baskets equipment: 1 x CT-10, 1 x CP-16/18, 1 x CB-7 and
 4 cutlery containers.
 Power: 6.65 kW.
 Dimensions: 600 x 600 x 1.200 mm.

DATA

Electric power	kW	6,65	Water consumption	lit/h	54
Electrical intake			Water pressure	Kg/cm ²	2 - 4
230V - 1 + N + T	2x6+T - 40 A		Steam power	kg/h	
230V - 3 + T	3x6+T - 40 A		Steam pressure	Kg/cm ²	
400V - 3 + N + T	4x4+T - 32 A		Air consumption	Nl/min	
Gas power	kcal/h		Air pressure	Kg/cm ²	
Gas power	kW		Length	mm	600
Natural Gas Consumption	m ³ /h		Depth	mm	600
Natural Gas pressure	g/cm ²		Height	mm	1200
LPG Consumption	Kg/h		Net weight	kg	69
LPG pressure	g/cm ²		Gross weight	kg	75
			Volume	m ³	0,6298



Distribuidor oficial: