



B° Sancholopetegui, 22
 Apdo. 17
 20560 OÑATI (ESPAÑA)
 Tel: +34 943 71 80 30
 Fax: +34 943 71 81 81

 www.fagorindustrial.com

DISHWASHER, FI-80

DESCRIPTION

Made of stainless steel.
 Hourly production: 800 dishes/h.
 Wash cycle: adjustable 0-120".
 Rotating wash and rinse systems.
 Heated by means of shielded elements.
 Wash pump for lower and upper systems, 590 W.
 Tank with 4,5 kW heating element.
 Built-in rinse water boiler (6 kW). Automatic rinse dispenser.
 Thermostatically adjusted. (wash temperature: 60 °C).
 Safety thermostat.
 Safety switch for hood opening. Adjustable legs.
 Baskets equipment: 1 x CT-10, 1 x CP-16/18 and 2 cutlery containers.
 Power: 11.10 KW
 Dimensions: 675 x 675 x 1400 mm.

Baskets equipment: 1 x CT-10, 1 x CP-16/18, 1 x CB-7 and
 4 cutlery containers.
 Power: 6.65 kW.
 Dimensions: 600 x 600 x 1.200 mm.

DATA

Electric power	kW	11,1	Water consumption	lit/h	54
Electrical intake			Water pressure	Kg/cm ²	2 - 4
230V - 1 + N + T	2x10+T - 60 A		Steam power	kg/h	
230V - 3 + T	3x6+T - 40 A		Steam pressure	Kg/cm ²	
400V - 3 + N + T	4x2,5+T - 25 A		Air consumption	Nl/min	
Gas power	kcal/h		Air pressure	Kg/cm ²	
Gas power	kW		Length	mm	675
Natural Gas Consumption	m ³ /h		Depth	mm	675
Natural Gas pressure	g/cm ²		Height	mm	1400
LPG Consumption	Kg/h		Net weight	kg	108
LPG pressure	g/cm ²		Gross weight	kg	124
			Volume	m ³	0,876



Distribuidor oficial: