



B° Sancholopetegui, 22
 Apdo. 17
 20560 OÑATI (ESPAÑA)
 Tel: +34 943 71 80 30
 Fax: +34 943 71 81 81

 www.fagorindustrial.com

DISHWASHER, FI-30

DESCRIPTION

Made of stainless steel.
 Hourly production: 320 dishes/h.
 Maximum diameter of dishes: Ø 32 cm.
 Wash cycle: 0-240".
 Rotating wash and rinse.
 Heated by means of shielded elements.
 Built-in rinse water boiler.
 Tank with 2.8 kW heating element.
 Tank capacity: 25 litres.
 Boiler with 2.8 KW heating element.
 Water consumption: 2.7 litres/rinse.
 Automatic rinse dispenser.
 Thermostatically adjusted. (wash temperature: 60 °C).
 Safety thermostat.
 Safety switch for door opening.
 Adjustable legs.
 Baskets equipment: 1 x CT-10, 1 x CP-16/18 and 1 cutlery containers.
 Power: 3.45 kW.

Dimensions: 600 x 600 x 810 mm.

DATA

| | | | | | |
|-------------------------|-------------------|------|-------------------|--------------------|--------|
| Electric power | kW | 3,45 | Water consumption | lit/h | 41 |
| Electrical intake | | | Water pressure | Kg/cm ² | 2 - 4 |
| 230V - 1 + N + T | 2x2,5+T - 20 A | | Steam power | kg/h | |
| 230V - 3 + T | 3x2,5+T - 20 A | | Steam pressure | Kg/cm ² | |
| 400V - 3 + N + T | 4x2,5+T - 20 A | | Air consumption | Nl/min | |
| Gas power | kcal/h | | Air pressure | Kg/cm ² | |
| Gas power | kW | | Length | mm | 600 |
| Natural Gas Consumption | m ³ /h | | Depth | mm | 600 |
| Natural Gas pressure | g/cm ² | | Height | mm | 820 |
| LPG Consumption | Kg/h | | Net weight | kg | 54 |
| LPG pressure | g/cm ² | | Gross weight | kg | 61 |
| | | | Volume | m ³ | 0,3902 |



Distribuidor oficial: