



B° Sancholopetegui, 22  
 Apdo. 17  
 20560 OÑATI (ESPAÑA)  
 Tel: +34 943 71 80 30  
 Fax: +34 943 71 81 81  
 ---  
 www.fagorindustrial.com

**DISHWASHER,  
 FI-48**

**DESCRIPTION**

Made of stainless steel.  
 Hourly production: 540 dishes/h.  
 Maximum diameter of dishes: Ø 32 cm.  
 Wash cycles: 120" and 180" fixed.  
 Rotating wash and rinse.  
 Heated by means of shielded elements.  
 Built-in rinse water boiler.  
 Tank with 2.8 kW heating element.  
 Tank capacity: 25 litres.  
 Boiler with 2.8 KW heating element.  
 Water consumption: 2.7 litres/rinse.  
 Automatic rinse dispenser.  
 Thermostatically adjusted. (wash temperature: 60 °C).  
 Safety thermostat.  
 Filters and trays in the wash tank.  
 Safety switch for door opening.  
 Adjustable legs.  
 Baskets equipment: 1 x CT-10, 1 x CP-16/18 and 4 cutlery containers.

Power: 3.45 kW.  
 Dimensions: 600 x 600 x 810 mm.

**DATA**

Electric power	kW	3,45	Water consumption	lit/h	54
Electrical intake			Water pressure	Kg/cm <sup>2</sup>	2 - 4
230V - 1 + N + T	2x2,5+T - 20 A		Steam power	kg/h	
230V - 3 + T	3x2,5+T - 20 A		Steam pressure	Kg/cm <sup>2</sup>	
400V - 3 + N + T	4x2,5+T - 20 A		Air consumption	Nl/min	
Gas power	kcal/h		Air pressure	Kg/cm <sup>2</sup>	
Gas power	kW		Length	mm	600
Natural Gas Consumption	m <sup>3</sup> /h		Depth	mm	600
Natural Gas pressure	g/cm <sup>2</sup>		Height	mm	820
LPG Consumption	Kg/h		Net weight	kg	60
LPG pressure	g/cm <sup>2</sup>		Gross weight	kg	67
			Volume	m <sup>3</sup>	0,3902



Distribuidor oficial: