



B° Sancholopetegui, 22
 Apdo. 17
 20560 OÑATI (ESPAÑA)
 Tel: +34 943 71 80 30
 Fax: +34 943 71 81 81

 www.fagorindustrial.com

DISHWASHER, FI-64 B

DESCRIPTION

Made of stainless steel.
 Hourly production: 720 dishes/h.
 Maximum diameter of dishes: Ø 32 cm.
 Wash cycles: 90" and 180" fixed.
 Main switch.
 Drain pump and drainage cycle.
 Rotating wash and rinse.
 Heated by means of shielded elements.
 Built-in rinse water boiler.
 Tank with 2.8 kW heating element.
 Tank capacity: 25 litres.
 Boiler with 6 KW heating element.
 Water consumption: 2.7 litres/rinse.
 Automatic rinse dispenser.
 Thermostatically adjusted. (wash temperature: 60 °C).
 Safety thermostat.
 Filters and trays in the wash tank.
 Safety switch for door opening.
 Adjustable legs.

Baskets equipment: 1 x CT-10, 1 x CP-16/18 and 4 cutlery containers.
 Power: 6.72 kW.
 Dimensions: 600 x 600 x 810 mm.

DATA

Electric power	kW	6,72	Water consumption	lit/h	54
Electrical intake			Water pressure	Kg/cm ²	2 - 4
230V - 1 + N + T	2x6+T - 40 A		Steam power	kg/h	
230V - 3 + T	3x2,5+T - 25 A		Steam pressure	Kg/cm ²	
400V - 3 + N + T	4x2,5+T - 20 A		Air consumption	Nl/min	
Gas power	kcal/h		Air pressure	Kg/cm ²	
Gas power	kW		Length	mm	600
Natural Gas Consumption	m ³ /h		Depth	mm	600
Natural Gas pressure	g/cm ²		Height	mm	820
LPG Consumption	Kg/h		Net weight	kg	60
LPG pressure	g/cm ²		Gross weight	kg	67
			Volume	m ³	0,3902



Distribuidor oficial: