



B° Sancholopetegui, 22
 Apdo. 17
 20560 OÑATI (ESPAÑA)
 Tel: +34 943 71 80 30
 Fax: +34 943 71 81 81

 www.fagorindustrial.com

1/1 GN REFRIGERATED WORK TABLE, MFP-135-GN

DESCRIPTION

Stainless steel exterior, AISI-304, 18/10, except rear panel.
 Stainless steel interior, AISI-304, 18/10, with rounded corners at the bottom.
 Stainless steel adjustable legs, AISI-304, 18/10. Rear guard of 10 cm.
 Equipped with 2 pairs of 1/1 GN guides and 1 grid per door.
 Rotating door-type grid panel.
 Working temperature: 0°C, +10°C at room temperature of 43°C.
 Removable, ventilated airtight compressor.
 R-134 A coolant.
 60-mm thick injected polyurethane insulation. Density 40 kg. No CFC.
 Copper evaporator with aluminium fins.
 Forced draught.
 Automatic evaporation of water during defrosting.
 Illuminated general switch.
 Electronic temperature and defrosting control and display.
 Doors with automatic locking device and fixed opening.
 Worktop with curved front.

Optional gastronorm accessories.
 Operating voltage 220/240 V - I - 50/60 Hz.
 N. of doors: 2.
 Capacity (litres): 300.
 Power: 275 W.
 Dimensions: 1.346 x 700 x 850 mm.

DATA

Electric power	kW	0,35	Water consumption	lit/h	
Electrical intake			Water pressure	Kg/cm ²	
230V - 1 + N + T	2x1,5+T - 2 A		Steam power	kg/h	
230V - 3 + T			Steam pressure	Kg/cm ²	
400V - 3 + N + T			Air consumption	Nl/min	
Gas power	kcal/h		Air pressure	Kg/cm ²	
Gas power	kW		Length	mm	1346
Natural Gas Consumption	m ³ /h		Depth	mm	700
Natural Gas pressure	g/cm ²		Height	mm	850
LPG Consumption	Kg/h		Net weight	kg	80
LPG pressure	g/cm ²		Gross weight	kg	87
			Volume	m ³	1,1001



Distribuidor oficial: