



FAGOR INDUSTRIAL

B° Sancholopetegui, 22  
 Apdo. 17  
 20560 OÑATI (ESPAÑA)  
 Tel: +34 943 71 80 30  
 Fax: +34 943 71 81 81  
 ---  
 www.fagorindustrial.com



## REFRIGERATED DISPLAY TRAY, VTP-139 P

### DESCRIPTION

Made from stainless steel, with anodised aluminium profile.  
 Glass sliding doors.  
 Protected internal lightning.  
 1/3 Gastronorm trays depth 40 mm included.  
 PVC sides with flat glass.  
 Unit or connection to unit on right hand side.  
 Ventilated air-tight compressor unit.  
 R-134 coolant.  
 Thermostat temperature control with indicator thermometer.  
 Illuminated general switch.  
 Working temperature: 0 °C, +6 °C at room temperature of 43°C.  
 Insulation of injected polyurethane. Density 40 kg. No CFC.  
 Operating voltage 220/240 V – I – 50/60 Hz.  
 Cold plate, static refrigeration.  
 Frontal straight glass.  
 Equipped with 6 containers 1/3 GN.  
 Refrigeration power: 170 W.  
 Dimensions: 1.395 x 400 x 250 mm.

### DATA

Electric power	kW	0,17	Water consumption	lit/h	
Electrical intake			Water pressure	Kg/cm <sup>2</sup>	
230V - 1 + N + T	2x1,5+T - 2 A		Steam power	kg/h	
230V - 3 + T			Steam pressure	Kg/cm <sup>2</sup>	
400V - 3 + N + T			Air consumption	Nl/min	
Gas power	kcal/h		Air pressure	Kg/cm <sup>2</sup>	
Gas power	kW		Length	mm	1395
Natural Gas Consumption	m <sup>3</sup> /h		Depth	mm	400
Natural Gas pressure	g/cm <sup>2</sup>		Height	mm	250
LPG Consumption	Kg/h		Net weight	kg	44
LPG pressure	g/cm <sup>2</sup>		Gross weight	kg	51
			Volume	m <sup>3</sup>	0,2577



Distribuidor oficial: