



FAGOR INDUSTRIAL

B° Sancholopetegui, 22
Apdo. 17
20560 OÑATI (ESPAÑA)
Tel: +34 943 71 80 30
Fax: +34 943 71 81 81

www.fagorindustrial.com



REFRIGERATED DISPLAY TRAY, VTP-175 P

DESCRIPTION

Made from stainless steel, with anodised aluminium profile.
Glass sliding doors.
Protected internal lightning.
1/3 Gastronorm trays depth 40 mm included.
PVC sides with flat glass.
Unit or connection to unit on right hand side.
Ventilated air-tight compressor unit.
R-134 coolant.
Thermostat temperature control with indicator thermometer.
Illuminated general switch.
Working temperature: 0 °C, +6 °C at room temperature of 43°C.
Insulation of injected polyurethane. Density 40 kg. No CFC.
Operating voltage 220/240 V – I – 50/60 Hz.
Cold plate, static refrigeration.
Frontal straight glass.
Equipped with 8 containers 1/3 GN.
Refrigeration power: 200 W.
Dimensions: 1.750 x 400 x 250 mm.

DATA

Electric power	kW	0,2	Water consumption	lit/h	
Electrical intake			Water pressure	Kg/cm ²	
230V - 1 + N + T	2x1,5+T - 2 A		Steam power	kg/h	
230V - 3 + T			Steam pressure	Kg/cm ²	
400V - 3 + N + T			Air consumption	Nl/min	
Gas power	kcal/h		Air pressure	Kg/cm ²	
Gas power	kW		Length	mm	1750
Natural Gas Consumption	m ³ /h		Depth	mm	400
Natural Gas pressure	g/cm ²		Height	mm	250
LPG Consumption	Kg/h		Net weight	kg	35
LPG pressure	g/cm ²		Gross weight	kg	42
			Volume	m ³	0,2061



Distribuidor oficial:

